"ArmoDock Solutions"

Easy, Safe, Solid.



Minidock – Steel and Aluminum Levellers Options for Loading Bays





Armo s.p.a. has developed day by day the quality of its production, the efficiency of its industrial organization and the experience of its staff. Mini dock levellers, manual levellers and accessories for loading bays are built, set up and checked in Italy: a product with all the features of quality typical of **MADE IN ITALY**.



Certificated

All Armo equipment is rigorously and repeatedly tested in our factories, and, if forseen, they are CE marked.



Guaranteed


All products are covered by a 24 months warranty, starting from the delivery date. The warranty can be extended.





Insured

ARMO is covered by a liability Insurance Policy for Industrial Companies.









Variant available on request

MINIDOCK

The Mini Dock is a manual operating with capacity 60 kN and hinged lip.

Main features

Armo **Mini Dock leveller** is the appropriate alternative to the classic Hydraulic Leveller to compensate small differences in height in a simple way and economically interesting, as well as loading trucks. Armo **Mini Docks** foreseen with bumpers as a standard option: the lip with length 350 mm, is designed to always have a free space to lean against the bed truck. All Armo's loading levellers are made in accordance to the EN 1398 rule.

Standard color: RAL 9005 BLACK.

Options: HOT-DIP GALVANIZATION – RAILINGS.

How does it work?

The operator on the dock edge manually opens the **Armo Mini Dock** pulling the standard lever and as soon as the frame gets open, the lip is extended automatically. Thanks to the lever, the frame opens, goes down and rests against the bed of the truck. During the loading/unloading operations, the leveller will follow the truck's movements automatically. At the end of those operations, the leveler must return in its normal rest position, by acting on the lever.

LIGHT- ALLOY LEVELLERS AT THE EDGE OF THE DOCK

CODE	DIMENSIONS					CAPACITY kq			
	length	Х	width	min.	max.	5			
AR-KBS.21.000	410	х	1250	- 70	+ 30	4000			
AR-KBS.21.012	535	х	1250	- 90	+ 45	4000			
AR-KBS.21.013	785	х	1250	- 120	+ 75	4000			
AR-KBS.21.002	910	х	1250	- 135	+ 90	4000			
AR-KBS.21.004	410	х	1500	- 70	+ 30	4000			
AR-KBS.21.014	535	х	1500	- 90	+ 45	4000			
AR-KBS.21.015	785	х	1500	- 120	+ 75	4000			
AR-KBS.21.006	910	х	1500	- 135	+ 90	4000			
AR-BSFV.23.006	Steel not painted rail with length 1000 - 2000 - 3000 mm								
AR-BSFZ.23.016	Galvanized rail with length 1000 - 2000 - 3000 mm								

AR-SKBS

AR-SKBS Light-Alloy Levellers: Due to the stress limits of the ergonomic lifting of 30 kg, all fixed and sliding light-alloy levellers operate manually with a safety block, up to maximum length of 815 mm, and springs screw up to a maximum length of 1565 mm. All levellers are provided with a vertical safety block system. Armo's light-alloy levellers are also equipped with a maneuvering bar, which is integrated to the leveller and placed to its lateral side.

AR-KBS

AR- KBS Light-Alloy Levellers: they are levellers, which moves through a steel welded rail at the top of the dock. In their rest position, they are vertical oriented and ensured avoiding a potential fall thanks to a block (EN 1398), but they could also be placed in vertical position at the edge of the dock. Due to the stress limits of the ergonomic lifting of 30 kg, the AR-KBS are available up to the maximum size indicated in the chart.


CODE			SIONS	WORKING RANGE		CAPACITY	
	length	Х	width	min.	max.	kg	
AR-SKBS.20.011	815	х	1250	- 120	+ 80	4000	
AR-SKBS.20.012	1315	х	1250	- 185	+ 140	2500	
AR-SKBS.20.013	1565	х	1250	- 215	+ 175	1750	
AR-SKBS.20.014	565	х	1500	- 90	+ 50	4000	
AR-SKBS.20.015	815	х	1500	- 120	+ 80	4000	
AR-SKBS.20.016	1065	х	1500	- 155	+ 110	4000	
AR-SKBS.20.017	1315	х	1500	- 185	+ 140	4000	
AR-SKBS.20.018	1565	х	1500	- 215	+ 175	4000	
AR-SKBS.22.002	Not painted rail with length 2000 - 3000 mm						
AR-SKBS.23.007	Galvanized rail with length 2000 - 3000 mm						



BALANCED STEEL LEVELLERS AT THE EDGE OF THE DOCK

Steel levellers RAL 5010, capacity kg. 5000-6000: Thanks to the springs screw, the horizontal and vertical position are perfectly balanced, even in case of considerable weights. This enables to use, due to their dimensions, steel levellers with a capacity of 5000 kg and 6000 kg. All levellers are provided with a mechanical safety block system in their vertical rest position. The maneuver is made thanks to a bar, which in its rest position is placed to the side of the leveller: the ergonomic stress is within 30 kg.

Options: hot-dip galvanization, sector lips for lateral inclination.



Lateral adaptation to the truck's inclination: the levellers larger than 1750 mm must follow the lateral inclination of the vehicle. This could be difficult for the balanced levellers because of the lack of the own weight. To solve this problem, all our levellers could be purchased with the option light-alloy "sectors lip".

FIXED le	AR-FBS.20						
SLIDING	AR-FBS.21						
CODE	DIMENSIONS			W.RA	NGE	CAPACITY	
	length	Х	width	min.	max.	kg	
.002	1500	х	1750	- 190	+ 140	5000	
.003	1500	х	2000	- 190	+ 140	5000	
.004	1750	х	1500	- 220	+ 175	5000	
.005	1750	х	1750	- 220	+ 175	5000	
.006	1750	х	2000	- 220	+ 175	5000	
.007	2000	х	1500	- 250	+ 205	5000	
.008	2000	х	1750	- 250	+ 205	5000	
.009	2000	х	2000	- 250	+ 205	5000	
AR-SFV.22.000	Steel not painted rail with length 1000 - 2000 - 3000 mm						
AR-SFZ.23.001	Galvanized rail with length 1000 - 2000 - 3000 mm						



Armo s.p.a.

Registered Office: Via Rosa di Luxemburg, 1 10093 Collegno (TO) - Italy *Operational Office*: Via Vittime di Bologna 10/16 10060 None (TO) - Italy

Capital Share € 1.000.000 i.v. c.c.i.a.a. n.667754 Registro società n. 4136/85 VAT # 04873070017

Tel. +39.011.71760.11 Fax +39.011.71760.19

e-mail: info@armoweb.com www.armoweb.com

Armo is also ...

- Dock levellers
- Tailor-made Lifting tables
- Maintenance & Service
- Industrial Doors
- Residential Sectional Doors

Ask our partner

